This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

- 1. (Currently Amended) Callous plane having a blade head (2) and a handle (3), where the callous plane (1) has an underside facing the body surface of a user when in working position, and an upper side facing away from said underside, and where a holding device (4) with a lower holding part (7) and an upper holding part (9) is provided in the blade head (2), in which a blade (5) can be held in such a manner that its cutting edge (6) intended for use to shave off callous skin is located on the underside of the callous plane (1), eharacterised in that wherein the lower holding part (7) is permanently connected to the handle (3) and displays an upward-pointing seat (8) for the blade (5), and in that the upper holding part (9) holds the blade tightly in the seat (8) with the help of a fixing device characterised in that the fixing device displays snap-in means for snap-fitting the upper holding part to the lower holding part.
- 2. (Currently Amended) Callous plane according to Claim 1, characterised in that the underside of the blade head (2) transitions smoothly from the lower holding part (7) into the underside of the handle (3).
- 3. (Currently Amended) Callous plane according to Claim 1 or 2, characterised in that the lower holding part (7) covers the entire underside of the held blade (5), apart from a middle section of the cutting edge (6) intended for use.

- 4. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 3, c h a r a c t e r i s e d i n t h a t the blade head (2) essentially covers the upper side of the held blade (5), apart from a middle section of the cutting edge (6) intended for use.
- 5. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 4, characterised in that the underside of the upper holding part (9) and the upper side of the lower holding part (7) display curved shapes running roughly parallel to each other, the neutral axis of which runs in a working direction (X) of the callous plane (1), such that the held blade is located between the holding parts (7, 9) under bending stress.
- 6. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 5, c h a r a c t e r i s e d i n t h a t the lower holding part (7) displays a blade opening (11), through which the cutting edge (6) of the blade (5) can be passed in such a way that at least a middle longitudinal section of the cutting edge (6) projects beyond the edge of the blade opening (11) on the underside of the lower holding part (7) by a small distance perpendicular to the working direction (X).
- 7. (Currently Amended) Callous plane according to Claim 6, characterised in that the undersides of both holding parts (7, 9) are curved, where the bend radius of the underside of the lower holding part (7) is smaller than the bend radius of the underside of the upper holding part (9), at least in the area of the blade opening (11).

- 8. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 7, characterised in that the fixing device displays a guide device for inserting the blade (5) into the seat (8), and for inserting the two holding parts (7, 9) into each other.
- 9. (Currently Amended) Callous plane according to Claim 8, characterised in that the guide device displays guide prongs (16) that are located at the corners of the seat (8) and extend upwards, where the held blade (5) and the upper holding part (9) laterally rest against the guide prongs (16).
- 10. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 9, c h a r a c t e r i s e d i n t h a t the fixing device displays a tongue-and-groove guide, by means of which the upper holding part (9) can be guided over the lower holding part (7).
- 11. (Currently Amended) Callous plane according to Claim 10, characterised in that the tongue-and-groove guide displays a guide rail (33) and a guide groove (34) with a dovetail-type cross-section.
- 12. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 11, characterised in that the fixing device displays snap in means for snap fitting the upper holding part (9) to the lower holding part (7) a pressure hollow is provided on the free end of the blade head and on the upper side of the upper holding part.
- 13. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 12, characterised in that a through-passage for collecting and ejecting shaved-off

callous skin particles is provided in the upper holding part, where the through-passage is located above the blade opening when in working postition pressure hollow (20) is provided on the free end of the blade head (2) and on the upper side of the upper holding part (9).

- 14. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 13, characterised in that the handle displays a handle part at its free end and a connecting section at its end facing the blade head, where an eyehole leading from the upper side to the underside is let into the connecting section in order to give a view of the body surface of a user to be treated a through passage (22) for collecting and ejecting shaved off callous skin particles is provided in the upper holding part (9), where the through passage (22) is located above the blade opening (11) when in working position.
- 15. (Currently Amended) Callous plane according to one of Claim[[s]] 1 to 14, c h a r a c t e r i s e d i n t h a t, for ergonomic adaptation, the handle part displays a section for the ball of the thumb with convex padded grips in its free end area and/or a section for the fingers with a finger recess on its end facing towards the connecting section the handle (3) displays a handle part at its free end and a connecting section (24) at its end facing the blade head (2), where an eyehole (28) leading from the upper side to the underside is let into the connecting section (24) in order to give a view of the body surface of a user to be treated.
- 16. (Currently Amended) Callous plane according to Claim 15, characterised in that the section for the fingers displays a rectangular cross-section shape with finger recesses

provided on all sides, for ergonomic adaptation, the handle part displays a section for the ball of the thumb (26) with convex padded grips (30) in its free end area and/or a section for the fingers with a finger recess (29) on its end facing towards the connecting section (24).

17. (Currently Amended) Callous plane according to Claim 16, characterised in that the <u>callous plane is made of plastic</u> section for the fingers (25) displays a rectangular eross sectional shape with finger recesses (29) provided on all sides.

18. Cancelled